

LISOFLOOR 4000

Colored or transparent protection for wood floors



The green power
for your surface

LisoChem SRL

Rue de Le Mesnil, 34 5670
Viroinval (Belgium)

Phone: +32 60 490 190

Mobile: +32 483 367 323

www.lisochem.com
info@lisochem.com

Manufacture & Office

Rue des Mousquetaires Gris 35
ZI de Mariembourg

5660 Belgium

Phone: +32 60 490 190

Mobile: + 32 483 367 323

CHARACTERISTICS

LisoFloor 4000 is composed of reactive polymers. This water-based solution provides excellent protection for wood floors, both indoors and out.

PRODUCT DESCRIPTION

LisoFloor 4000 complies with worldwide VOC standards. LisoFloor 4000, while giving a satin or gloss finish, colored or transparent, will protect your wood floor. Easy roller application.

Excellent durability. Greatly increased wear resistance. Will not flake or discolor. Water-based, solvent-free product with very low VOC emissions.

Interior or exterior use. For all types of wood. Do not polish or burnish this product.

BENEFITS

LisoFloor 4000 :

- Product based on a range of new water-based resins
- Excellent resistance to abrasion and dust
- Excellent surface hydrophobicity and oleophobia
- Highly resistant to stains (oil, vinegar, lemon, acid, base,)
- Water-based, solvent-free product with very low VOC emissions

LISO FLOOR 4000

Colored or transparent protection for wood floors

APPLICATION

LisoFloor 4000 can be applied indoors or outdoors. For all types of wood. Do not polish or burnish this product.

Thoroughly sand the surface in the direction of the grain before application. The surface must be free of all wood particles and dust.

Apply 1 coat of LisoFloor 4000 with a roller (consumption depending on wood porosity).

Allow to dry for at least 45 minutes.

Apply a 2nd coat of LisoFloor 4000 by roller (consumption depending on the porosity of the wood).

The treated surface will be accessible to pedestrians after 24 hours and to all traffic 8 days after application.

SECURITY

Please refer to the safety data sheet :

- Keep out of reach of children
- Protect from freezing
- Wear gloves and safety glasses
- Cover all metal and glass parts before application

PROPERTIES

Transparent

Density : 1,1

Shelf life: 1 year in original, closed container

PACKAGING

Bucket..... 20L

Lisochem S.R.L. Tous droits réservés.

Date de révision : 15-05-2024